

## DOP-UKCA-DEKO WOOD 2 mm-558

**1. Unique identification code of the product-type:**

Connecting flue pipes  
EN 1856-2:2009

**2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):**

### DEKO WOOD 2 mm

1.0 Model painted steel 2 mm thickness	Ø130	T450 N1 D Vm L01200 G(390) NM
1.0 Model painted steel 2 mm thickness	Ø150	T450 N1 D Vm L01200 G(450) NM
1.0 Model painted steel 2 mm thickness	Ø180	T450 N1 D Vm L01200 G(540) NM
1.0 Model painted steel 2 mm thickness	Ø200	T450 N1 D Vm L01200 G(600) NM

**3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:**

Convey the products of combustion from heating appliances to the chimney

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):**

DINAK S.A.  
Camiño do Laranxo, 19  
36216, Vigo (SPAIN)  
dinak@dinak.com  
tlf: +34 986 452 526

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

Not applicable

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in the Construction Products Regulation 2011 (retained EU law EUR 305/2011) as amended, Annex V:**

System 2+

**7. UK Approved product certification body TÜV SÜD BABT unlimited No.0168, performed the initial inspection of the manufacturing plant and of the factory production control and continuous surveillance; assessment and evaluation of factory production control; and issued the certificate of conformity of the factory production control**

**8. Declared performance**

Essential Characteristics	Performance	Designated Standard
Compressive strength Chimney Sections, fittings and supports	NPD	EN 1856-2:2009
Flexural tensile strength (only for means of connection for chimney sections and fittings)	NPD	EN 1856-2:2009
Non vertical installation	NPD	EN 1856-2:2009
Resistance to fire	T450 – G	EN 1856-2:2009
Gas tightness/leakage	N1	EN 1856-2:2009
Flow resistance of chimney sections, fittings and terminals	According to EN 13384-1	EN 1856-2:2009
Thermal shock resistance Soot fire resistance	Yes	EN 1856-2:2009

## DOP-UKCA-DEKO WOOD 2 mm-558

Thermal performance under normal operating conditions	T450	
<b>Durability</b>		EN 1856-2:2009
Water and vapour diffusion resistance	No	
Condensate penetration resistance	No	
Against corrosion	Vm	
<b>Freeze thaw resistance</b>	Yes	EN 1856-2:2009

**9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.**

**This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

**Signed for and on behalf of the manufacturer by:**

Íñigo A. Canoa (General Manager)

Vigo, 1<sup>st</sup> September 2022