



Industrie Service

# CERTIFICATE

0036 CPD 90220 040

In compliance with the Directive 89/106/EEC of the Council of European Communities of 21<sup>st</sup> December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to the construction products (Construction Products Directive – CPD) amended by the Directive 93/68/EEC of the Council of European Communities of 22<sup>nd</sup> July 1993, it has been stated that the construction product

## Connecting flue pipe DINAK XT models

1.4404/316L	EN 1856-2	T200 H1 W V2 L50XXX OXXX NM
1.4521/444	EN 1856-2	T200 H1 W V2 L99XXX OXXX NM
1.4162/S32101	EN 1856-2	T200 H1 W V2 L99XXX OXXX NM
1.4301/304	EN 1856-2	T200 H1 W Vm L20XXX OXXX NM
1.0226/AS120	EN 1856-2	T200 H1 W Vm L05XXX OXXX NM

1) for details of designation see second page of certificate

produced by

**DINAK S.A.**  
**Camiño do Laranxo, 19**  
**E-36 216 Vigo**

in the factory

**DINAK S.A.**  
**E-36 216 Vigo**

is submitted to

- the **initial type testing**, performed by TÜV SÜD Industrie Service GmbH, test reports A 1839-01/10, A 1839-02/11, A 1814-00/09, A 1824-00/09 and A 1895-00/10 as well as
- a **factory production control**

The Notified Body TÜV SÜD Industrie Service GmbH has performed the initial inspection of the factory and the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of factory production control described in Annex ZA of the standard

**EN 1856-2: 2009-06**

were applied.

This certificate was first issued on 2011-12-29 and - with respect to the conditions of the certification contract - remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly.

Munich, 2011-12-29

.....  
 J. Steiglechner





Industrie Service

Connecting flue pipe DINAK XT		EN1856-2			
diameter		Different models			
		1.4404/316L	1.4521/444	1.4162/S32101	
DN 125	T200 H1 W	V2 L50040	V2 L99040	V2 L99050	O 375 NM
DN 150	T200 H1 W	V2 L50040	V2 L99040	V2 L99050	O 450 NM
DN 175	T200 H1 W	V2 L50040	V2 L99040	V2 L99050	O 525 NM
DN 200	T200 H1 W	V2 L50040	V2 L99040	V2 L99050	O 600 NM
DN 250	T200 H1 W	V2 L50040	V2 L99040	V2 L99050	O 750 NM
DN 300	T200 H1 W	V2 L50040	V2 L99040	V2 L99050	O 900 NM
DN 350	T200 H1 W	V2 L50050	V2 L99050	V2 L99050	O 1050 NM
DN 400	T200 H1 W	V2 L50050	V2 L99050	V2 L99050	O 1200 NM
DN 450	T200 H1 W	V2 L50050	V2 L99050	V2 L99050	O 1350 NM
DN 500	T200 H1 W	V2 L50060	V2 L99060	V2 L99060	O 1500 NM
DN 550	T200 H1 W	V2 L50060	V2 L99060	V2 L99060	O 1650 NM
DN 600	T200 H1 W	V2 L50060	V2 L99060	V2 L99060	O 1800 NM
DN 650	T200 H1 W	V2 L50080	V2 L99080	V2 L99080	O 1950 NM
DN 700	T200 H1 W	V2 L50080	V2 L99080	V2 L99080	O 2100 NM
DN 750	T200 H1 W	V2 L50080	V2 L99080	V2 L99080	O 2250 NM
DN 800	T200 H1 W	V2 L50080	V2 L99080	V2 L99080	O 2400 NM
DN 850	T200 H1 W	V2 L50080	V2 L99080	V2 L99080	O 2250 NM
DN 900	T200 H1 W	V2 L50080	V2 L99080	V2 L99080	O 2700 NM
DN 950	T200 H1 W	V2 L50080	V2 L99080	V2 L99080	O 2850 NM
DN 1000	T200 H1 W	V2 L50080	V2 L99080	V2 L99080	O 3000 NM
		1.4301/304	1.0226/AS120		
DN 125	T200 H1 W	Vm L20040	Vm L05040		O 375 NM
DN 150	T200 H1 W	Vm L20040	Vm L05040		O 450 NM
DN 175	T200 H1 W	Vm L20040	Vm L05040		O 525 NM
DN 200	T200 H1 W	Vm L20040	Vm L05040		O 600 NM
DN 250	T200 H1 W	Vm L20040	Vm L05040		O 750 NM
DN 300	T200 H1 W	Vm L20040	Vm L05040		O 900 NM
DN 350	T200 H1 W	Vm L20050	Vm L05050		O 1050 NM
DN 400	T200 H1 W	Vm L20050	Vm L05050		O 1200 NM
DN 450	T200 H1 W	Vm L20050	Vm L05050		O 1350 NM
DN 500	T200 H1 W	Vm L20060	Vm L05060		O 1500 NM
DN 550	T200 H1 W	Vm L20060	Vm L05060		O 1650 NM
DN 600	T200 H1 W	Vm L20060	Vm L05060		O 1800 NM
DN 650	T200 H1 W	Vm L20080	Vm L05080		O 1950 NM
DN 700	T200 H1 W	Vm L20080	Vm L05080		O 2100 NM
DN 750	T200 H1 W	Vm L20080	Vm L05080		O 2250 NM
DN 800	T200 H1 W	Vm L20080	Vm L05080		O 2400 NM
DN 850	T200 H1 W	Vm L20080	Vm L05080		O 2250 NM
DN 900	T200 H1 W	Vm L20080	Vm L05080		O 2700 NM
DN 950	T200 H1 W	Vm L20080	Vm L05080		O 2850 NM
DN 1000	T200 H1 W	Vm L20080	Vm L05080		O 3000 NM